



General Product Specifications

Eureka Jewel Inbuilt & Jindara Spectre Inbuilt

Dimensions and Specifications	
Overall Dimension (Height)	692 mm
Overall Dimension (Width)	875 mm
Fascia Depth	16 mm
Rear Casing Dimension (Height)	644 mm
Rear Casing Dimension (Width)	751 mm
Rear Casing Dimension (Depth)	708 mm
Firebox Dimension (Height)	350 mm
Firebox Dimension (Width)	520 mm
Firebox Dimension (Depth)	538 mm
Door Opening Dimension (Height x Width)	258 x 541mm
Glass Viewing Size (Height x Width)	285 x 570mm
Flue Size	175mm
Back of fascia to flue centre	354 mm
Shipping weight	240kg
Linings	Cast Iron Liners on walls
Baffle thickness	8mm
Glass Type	Flat, toughened 5mm ceramic
Hearth & Clearance requirements	
Min. Hearth Width	940 mm
Min. Hearth Depth	1890 mm
Min. Hearth Thickness	32 mm
Min. In Front Of Unit	570 mm
Clearance to Mantle Upright	205 mm
Clearance to Mantel Shelf (from appliance base)	1127 mm
Clearance to Mantel Breast Plate (from appliance	4427
base) Emissions and Effic	1127 mm
	1.2g/kg 62%*
Efficiency Roak Output	
Peak Output	25+kw *Peak efficiency % quoted
	reak emciency % quoted

CLEARANCES AND SPECIFICATIONS PROVIDED IN THIS TABLE ARE FOR REFERENCE ONLY. ALWAYS REFER TO THE OWNER'S MANUAL FOR EXACT SPECIFICATIONS PRIOR TO INSTALLATION