



## **General Product Specifications**

## Eureka Solitaire FS SRS3 & Jindara Mallee FS SRS2

Dimensions and Specifications	
Overall Dimension (Height)	825 mm
Overall Dimension (Width)	850 mm
Overall Dimension (Depth)	620 mm
Firebox Dimension (Height)	399 mm
Firebox Dimension (Width)	636 mm
Firebox Dimension (Depth)	423 mm
Door Opening Dimension (Height x Width)	262 x 559mm
Glass Viewing Size (Height x Width)	270 x 580mm
Flue Size	175mm
Back of Heater to Flue Centre	180 mm
Shipping weight	220kg
Linings	Firebricks on walls
Baffle thickness	8mm
Glass Type	Bay, toughened 5mm ceramic
Hearth & C	learance requirements
Min. Hearth Width	960 mm
Min. Hearth Depth	1075 mm
Min. Hearth Thickness	6 mm
Min. In Front Of Unit	450 mm
Rear Clearance	100 mm*
Side Clearance	425 mm
Corner Clearance	100 mm
	* denotes standard flue shield required (included in wood heater)
Emissi	ons and Efficiency
Emissions	0.9g/kg
Efficiency	66%*
Peak Output	20kw
	*Peak efficiency % quoted

CLEARANCES AND SPECIFICATIONS PROVIDED IN THIS TABLE ARE FOR REFERENCE ONLY. ALWAYS REFER TO THE OWNER'S MANUAL FOR EXACT SPECIFICATIONS PRIOR TO INSTALLATION